



## Rope Reel

Item number	Model	Outside diameter ×root diameter ×width of coil (mm)	Weight (kg)
15111	SE-1	Φ480×Φ220×340	13
15112	SE-2	Φ720×Φ400×640	30
15113	SE-3	Φ850×Φ400×640	40
15114	SE-4	Φ950×Φ400×640	50
15115	SE-5	Φ1100×Φ400×640	55
15116	SE-6	Φ1200×Φ400×640	59

**Uses:**To load wire rope



## Cradle Reel Stand

Item number	Model	Outside diameter×root diameter×width of coil (mm)	Weight (kg)
15101	SE-1J	1000×420×350	12
15102	SE-2J	1400×720×530	16
15103	SE-3J	1400×720×530	16
15104	SE-4J	1660×720×630	20
15105	SE-5J	1750×730×680	30
15106	SE-6J	1840×730×710	39

**Uses:**To support rope reel

**Notes:**Matched model is one to one corresponding.



## Upright Payout Turntable

Item number	Model	Diameter of trestle (mm)	Bearing power(kg)	Weight(kg)	features
51311	SIW-1	Φ500	1000	36	Small cover slab
15132	SIW-3A	Φ800	3000	70	
15133	SIW-3B	Φ1000	3000	102	
15134	SIW-3	Φ800	3000	92	Big cover slab
15135	SIW-5	Φ1500	5000	129	Small cover slab



## Integrated Reel Stand

Item number	15141	15142	15143	
Model	SIPZ3A	SIPZ5A	SIPZ-7	
Applicable reel	Diameter of coil (mm)	Φ900~1600	Φ1600~2400	Φ1800~2500
	Width of coil (mm)	≤1350	≤1350	≤1700
	Diameter of axle hole (mm)	Φ65-100	Φ65-100	Φ120
	Maximum weight (kg)	3000	5000	7000
Brake torque (N.m)	1000	1000	2000	
Speed (m/min)	80	80	80	
Weight (kg)	200	215	480	

### Notes:

- 1.To support reel in tension releasing wire or mechanically pull wire and to brake the reel
- 2.Can be disassembled into 3 pieces ,convenient for transportation.
- 3.SIPZ-7 is double -disc brake.





## Hydraulic Conductor Reel Stands

Item number	15151	15152	15153
Model	DW2240A	SIPZ-7H	SIPZ-7K
Applicable reel	Diameter of coil (mm)	Φ1250~2240	Φ1250~2500
	Max width of coil (mm)	1400	1400
	Diameter of axle hole (mm)	Φ80-125	Φ80-125
	Maximum weight (kg)	5000	7000
Max working torque (N.m)	1200	2000	2500
Max Speed (rpm)	45	45	45
Axle diameter(mm)	Φ76	Φ76	Φ69
Weight (kg)	270	350	350
Length of hydraulic tube(m)	13	13	13

**Notes:** Connect with hydraulic tensioner or hydraulic puller tensioner through quick coupling



15151



15153



15152

## Large Capacity Hydraulic Conductor Reel Stands

Item number	15155	15158
Model	SIYZ10	SIYZ15
Applicable reel	Diameter of coil (mm)	Φ2000~3000
	Max width of coil (mm)	1700
	Diameter of axle hole (mm)	Φ125-130
	Maximum weight (kg)	10000
Max working torque (N.m)	3300	4500
Max Speed (rpm)	45	45
Axle diameter(mm)	Φ94	Φ119
Weight (kg)	597	789
Length of hydraulic tube(m)	15	20



15155

**Notes:** Connect with hydraulic tensioner or hydraulic puller tensioner through quick coupling

## Simple Reel Payout Stand

Item number	Model	Rated load (kN)	Range of adjustable height (mm)	Weight (kg)	Feature
15191	SIL-1	10	450-650	22	Pillarstyle
15192	SIL-3	30	600-900	24	
15193	SIL-5	50	900-1300	27	
15201	SIK-3	30	400-1000	30	Framestyle
15202	SIK-5	50	710-1270	44	
15211	SIL-3A	30	620-1000	28	Pillar base-Frame style
15212	SIL-5A	50	900-1300	35	

**Features:** To adjust reel by screw mandrel .light ,handy and practicable .it fit releasing wire manually.

**Notes:** 1.It has to be used in pairs.

2.Can purchase our axle (Φ60×2200mm seamless steel pipe ),the item number is 15191G



SIL Pillar style



SIK Frame style



SIL-A Pillar base-Frame style

## Portable Reel Stands

Item number:15222

Suitable hoop diameter(mm):Φ950

Dimension(mm):988×988×415

Height(mm):415

Max rope storage(kg):100

Net weight(kg):10.5

**Uses:**It suitable for installation work which need less conductor or wire rope.

